

Assembly Instructions C1-SF450S-X LADDERBACK SIDE CHAIR

PARTS LIST

PART NO	FIGURE	DESCRIPTION	Q'TY
DS450SCH-01		HARDWARE BAG	1 Pce
DS450SCH-02		CHAIR BACK	1 Pce
DS450SCH-03		WOOD SEAT	1 Pce
DS450SCH-04		SEAT FRAME	1 Pce
DS450SCH-05		FRONT LEG (RIGHT)	1 Pce
DS450SCH-06		FRONT LEG (LEFT)	1 Pce




Assembly Instructions C1-SF450S-X LADDERBACK SIDE CHAIR



ASSEMBLY:

- 1. Position the Chair Back on a soft surface such as a carpet. Place the Seat Frame (Wood seat is pre- attached to the seat frame in assembly) on to the middle rail of the Chair Back with the dowel fully Inserted into the pre-drilled hole.
- 1.1. Insert 70mm JCBC Bolt a Lock Washer and a Flat Washer into the pre-drilled holes on the rear corner block of the seat frame.
- 1.2. Insert the 40mm JCBC Bolt a Lock Washer and a Flat Washer through the rear pre-drilled holes on the seat frame.
- 2. Insert the 70mm JCBC Bolt through a Lock Washer, a Flat Washer and the pre-drilled holes of Corner Block into the pre-drilled holes on the Front Leg, use the provided Allen Key. But do not fully tighten the bolts yet.



(STEP 3)

Turn the chair to standing position. Check it's balance and tighten all screw and bolts to complete the assembly.

